



H170L

Cabinet Color	Silver & Black
Panel	TFT Active Matrix LCD, Slim Cabinet VIS: 17" (43.2cm), Diagonal Hard Coating (3H), Anti-glare Treatment
Pixel Pitch	0.264mm x 0.264mm
Display Area	338mm x 270mm
Brightness	300 cd/m2 (typ)
Contrast Ratio	500:1 (typ)
Response Time	8ms (typ)
Viewing Angle	Horizontal: 160 Degrees (CR>5) Vertical: 145 Degrees (CR>5)
Compatibility	VESA, SXGA, XGA, SVGA, VGA Mac® Equipped With VGA Port
Scanning Frequency	Horizontal: 30K~83KHz Vertical: 55~75 Hz
Pixel Frequency	135MHz
Maximum Resolution	1280x1024@75Hz
Recommended Resolution	1280x1024@60Hz
Resolutions Supported	720x400@70Hz, 640x480@60/67/75Hz, 800x600@56/60/72/75Hz, 832x624@75Hz, 1024x768@60/70/75Hz, 1280x1024@60/75Hz
Color	16M
Signal Input	Video: 0.7Vp-p, RGB Analog Separate Sync: TTL Level H/V Sync: Positive / Negative
Connectors	RGB Signal: 15-pin D-sub (3-Pin Plug CEE22)
Power Source	Universal 100~240VAC, 50/60Hz (Internal Power Supply)
Power Consumption	45Watts (Max.)
Plug & Play	DDC2B
EPA ENERGY STAR®	Yes
User Control	Menu, Down, Up, Auto-Adjust/Select, Power
OSD Function	Auto Adjust, Contrast, Brightness, Color Adjust, Information, Image Adjust, Setup Menu, Memory Recall,
OSD Languages	English, French & Spanish
Regulations	cULus, FCC, CE, ISO13406-2
Other Features	VESA 100mm Wall Mount Compliant*, Kensington Security Slot
Dimensions (WxHxD mm)	Monitor: 372x369x184; Carton 435x415x150
Dimensions (WxHxD inches)	Monitor: 14.6x14.5x7.2; Carton: 17.2x16.3x5.9
Monitor Dimensions w/o Base (WxHxD)	372x330x68mm; 14.6x13.0x2.7 inches
Weight	8.6 lbs (3.9kgs) Net 11.0 Lbs (5.0kgs) Gross
Loading Qty w/pallet	20' = 840 pcs.; 40' Std = 1820 pcs.
UPC Code	685417101580